
MODEL	INDOOR UNIT		DP-AH60UMR4	
	OUTDOOR UNIT		DP-AC60SMR4	
			Cooling	Heating
Rated Capacity (Min. ~ Max.)		W	16120	N/A
		Btu/h	55000	N/A
Rated Running Current		A	20.9	N/A
Rated Power Consumption		W	4700	N/A
EER2		Btu/h/W	11.7	N/A
SEER2			14.3	N/A
COP		W/W	N/A	N/A
HSPF2			N/A	N/A
Power Factor (Rated)			N/A	
Piping Connections	Liquid	inch (mm)	3/8	
	Gas	inch (mm)	7/8	
Refrigerant	Type		R454B	
	Charge	oz (kg)	121.7(3.45)	
Max. Interunit Piping Length		ft (m)	164 (50)	
Max. Interunit Height Difference		ft (m)	66 (20)	
Chargeless		ft (m)	25 (7.6)	
Amount of Additional Charge of Refrigerant		oz/ft (g/m)	0.69(64.2)	
INDOOR UNIT			**DP-AH60UMR4**	
Front Panel Colour			HIGH GLOSS GRAY	
Airflow Rate	1st	CFM	/	
	2nd	CFM	1170	
	3rd	CFM	1388	
	4th	CFM	1549	
	5th	CFM	1707	
Sound Pressure Level (H/M/L/Q)		dBA	57	
Fan	Type		centrifugal	
	Drive		DIRECT	
	Speed		2nd, 3rd, 4th, 5th gear	
Fan Motor	Type		ECM	
	Motor Output	W	560	
	Running Current (Rated)	A	5.6	
Air Direction Control			Bottom return air, top outlet air	

Air Filter			/
Dimensions (W xH x D)		**inch (mm)**	22x53-1/8x24-1/2 (560×1350×623)
Weight		**lbs (kg)**	170(77)
Condensate Drain Size（NPT）		**inch (mm)**	3/4(19)
OUTDOOR UNIT			**DP-AC60SMR4**
Casing Color			HIGH GLOSS GRAY
Airflow Rate	**High**	**CFM**	4000
Sound Pressure Level		**dBA**	65
Fan	**Type**		PROPELLER
	Drive		DIRECT
Fan Motor	**Type**		PSC
	Index of protection (IP)		24
	Insulation Grade		F
	Running Current (Rated)	**A**	1.5
	Motor Output	**W**	230
	Poles		6
Compressor	**Type**		Scroll
	Model		YBH049KAA
	Oil type		POE
	Oil amount	**oz (cm3)**	43.3 (1280)
Heat Exchanger Type			FIN TUBE
Dimensions (W x H x D)		**inch (mm)**	29-1/7x32-7/8x29-1/7(740x 835×740)
Weight		**lbs (kg)**	206(93.4)

Indoor Unit

Model : DP-AH60UMR4

FOR ILLUSTRATIVE PURPOSES ONLY





Note: Dimension in inch (mm)


Outdoor Unit


Model : DP-AC60SMR4


FOR ILLUSTRATIVE PURPOSES ONLY











Note:Dimension in inch(mm)

Electric Characteristic

Unit Combination		Power Supply		Indoor Unit		IFM		Outdoor Unit		COMP		OFM	
Indoor Unit	Outdoor Unit	Hz-Volts	Voltage Range	MCA	MOP	kW	MOC	MCA	MOP	RHz	A	kW	MOC
DP-AH60UMR4	DP-AC60SMR4	60Hz-208/230V	MAX. 60Hz 253V MIN. 60Hz 198V	7.20	10	0.56	5.6	37.0	60.0	60	29.1	0.23	1.5

Symbols:

MCA : Minimum Circuit Amps (A)
MOP : Maximum Overcurrent Protection (A)
COMP : Compressor
RHz : Rated Operating Frequency (Hz)
A : Compressor Input Current (A)
OFM : Outdoor Fan Motor
IFM : Indoor Fan Motor
kW : Fan Motor Rated Output (kW)
MOC : Maximum Operating Current (A)

Notes:

1. RHz is the max frequency that comes in cooling operation and heating operation.
2. RLA is the max current that comes in cooling operatio and heating operation.
3. Maximum allowable voltage that is unbalance between phases is 2%.
4. Select wire size based on the larger value of MCA.
5. Use circuit breaker instead of fuse