



FILTER DRIER



DEPLUSWORLD

 WWW.DEPLUSWORLD.COM



FILTER DRIER SPECIFICATION

FOR USE WITH CFC,
HFC AND HCFC
REFRIGERANTS LISTED IN
CAN/CSA B52, ANSI/ASHRAE 34
AND ANSI/ASHRAE 15 SEC 9.2
WHERE THE SATURATION VAPOR
PRESSURE AT 125°F (HIGH SIDE)
AND 80°F (LOW SIDE) IN LESS
THAN THE MAXIMUM DESIGN
WORKING PRESSURE.
AFTER CHARGING MARK UNIT
WITH REFRIGERANT TYPE
AND OIL TYPE

DP-163S	Description	Connections Size & Type	Refrigeration				Air Conditioning		
			Commercial Low Temp Equipment				Field Replacement or OEM Installation		
			R-134A	R22	R404A, R-507	R290	R-134A	R-22, R407C, R410A	R290
			1~2	1-1/2~3	3/4~2	1-1/2~3	1~5	1-1/2~5	1-1/2~5
	162	1/4SAE							
	162S	1/4ODF							
	163	3/8SAE							
	163S	3/8ODF							
	164	1/2SAE							
	164S	1/2ODF							
	165	5/8SAE							
	165S	5/8ODF							

DP-083S	Description	Connections Size & Type	Refrigeration				Air Conditioning		
			Commercial Low Temp Equipment				Field Replacement or OEM Installation		
			R-134A	R22	R404A, R-507	R290	R-134A	R-22, R407C, R410A	R290
			1~2	1-1/2~3	3/4~2	1-1/2~3	1~5	1-1/2~5	1-1/2~5
	083S	3/8SAE							
	162	1/4SAE							
	162S	1/4ODF							
	163	3/8SAE							
	163S	3/8ODF							
	164	1/2SAE							
	164S	1/2ODF							
	165	5/8SAE							
	165S	5/8ODF							