


MODEL	INDOOR UNIT		DP-FR30UMR4	
	OUTDOOR UNIT		DP-AC30SMR4	
			Cooling	Heating
Rated Capacity (Min. ~ Max.)	W		8030	N/A
	Btu/h		27400	N/A
Rated Running Current	A		10	N/A
Rated Power Consumption	W		2340	N/A
EER2	Btu/h/W		11.7	N/A
SEER2			14.3	N/A
COP	W/W		N/A	N/A
HSPF2			N/A	N/A
Power Factor (Rated)			N/A	
Piping Connections	Liquid	inch (mm)	3/8	
	Gas	inch (mm)	3/4	
Refrigerant	Type		R454B	
	Charge	oz (kg)	81.1(2.3)	
Max. Interunit Piping Length	ft (m)		164 (50)	
Max. Interunit Height Difference	ft (m)		66 (20)	
Chargeless	ft (m)		25 (7.6)	
Amount of Additional Charge of Refrigerant	oz/ft (g/m)		0.69(64.2)	
INDOOR UNIT			DP-FR30UMR4	
Front Panel Colour			HIGH GLOSS GRAY	
Airflow Rate	1st	CFM	/	
	2nd	CFM	836	
	3rd	CFM	965	
	4th	CFM	1095	
	5th	CFM	1208	
Sound Pressure Level (H/M/L/Q)		dBA	55	
Fan	Type		centrifugal	
	Drive		DIRECT	
	Speed		2nd, 3rd, 4th, 5th gear	
Fan Motor	Type		ECM	
	Motor Output	W	373	
	Running Current (Rated)	A	4.2	

Air Direction Control			Front return air, top outlet air
Air Filter			/
Dimensions (W xH x D)	inch (mm)	22x39-3/5x19 (559×1006×485)	
Weight	lbs (kg)	110(50)	
Condensate Drain Size (NPT)	inch (mm)	3/4(19)	
OUTDOOR UNIT			DP-AC30SMR4
Casing Color			HIGH GLOSS GRAY
Airflow Rate	High	CFM	2200
Sound Pressure Level		dBA	63
Fan	Type		PROPELLER
	Drive		DIRECT
Fan Motor	Type		PSC
	Index of protection (IP)		24
	Insulation Grade		F
	Running Current (Rated)	A	1.5
	Motor Output	W	160
	Poles		6
Compressor	Type		Scroll
	Model		YPH024KAA
	Oil type		POE
	Oil amount	oz (cm3)	25 (740)
Heat Exchanger Type			FIN TUBE
Dimensions (W x H x D)	inch (mm)	23-3/5x25x23-3/5(600 x 635x 600)	
Weight	lbs (kg)	134(60.8)	

Indoor Unit

Model : DP-FR30UMR4


FOR ILLUSTRATIVE PURPOSES ONLY



Note: Dimension in inch (mm)

Outdoor Unit

Model : DP-AC30SMR4



Unit Combination		Power Supply		Indoor Unit		IFM		Outdoor Unit		COMP		OFM	
Indoor Unit	Outdoor Unit	Hz-Volts	Voltage Range	MCA	MOP	kW	MOC	MCA	MOP	RHz	A	kW	MOC
DP-FR30UMR4	DP-AC30SMR4	60Hz-208/230V	MAX. 60Hz 253V MIN. 60Hz 198V	4.50	6	0.373	3.2	18.0	30.0	60	13	0.16	1.5

Symbols:

MCA	: Minimum Circuit Amps (A)
MOP	: Maximum Overcurrent Protection (A)
COMP	: Compressor
RHz	: Rated Operating Frequency (Hz)
A	: Compressor Input Current (A)
OFM	: Outdoor Fan Motor
IFM	: Indoor Fan Motor
kW	: Fan Motor Rated Output (kW)
MOC	: Maximum Operating Current (A)

Notes:

1. RHz is the max frequency that comes in cooling operation and heating operation.
2. RLA is the max current that comes in cooling operation and heating operation.
3. Maximum allowable voltage that is unbalance between phases is 2%.
4. Select wire size based on the larger value of MCA.
5. Use circuit breaker instead of fuse